



FR-920 Finish Remover

MAINTENANCE PRODUCTS TECHNICAL DATA

Excelsior FR-920 Vinyl Flooring Finish Remover is a highly concentrated finish remover specifically designed to remove topically applied flooring finishes from vinyl resilient flooring products

Product Type	Finish Remover for Vinyl Floor Coverings
Characteristics	Clear, Colorless Liquid
Packaging	1 Gallon Unit
ASTM D7149 - Freeze Thaw Stability	Up to 5 Cycles, Down to 0° F
SCAQMD Rule 1113	≤ 0.1 grams/liter VOC Content
pH	12, When Properly Diluted
Dilution Ratio	32 - 64 oz. per Gallon
Coverage Range	100 - 150 sq. ft. per Diluted Gallon
<i>Coverages will vary depending upon dilution rate, flooring surface and applicator.</i>	
Application Method	Pump-Up Sprayer, String Mop
Dwell Time	5 - 10 Minutes
<i>Dwell time will vary with conditions; additional layers of finish will require additional time to break down the finish for removal.</i>	
Shelf Life	18 Months from Manufacturing Date

Reading the Date Code 12321

The first 3 numbers indicate the Julian date of production (123), the last 2 numbers indicate the year (21)

On the carton it is printed on the upper right corner on a side panel

On the bottle it is printed above the label

Service & Storage Temperature	60° - 85° F
--	-------------

Shelf Life depends on proper storage within service & storage temperatures in unopened container

The following information is provided as general guidance, always refer to the current care & maintenance information on the product website for the resilient flooring being maintained for complete and detailed information

Approved Flooring Products	LVT/LVP Solid Vinyl Tiles Quartz Flooring Vinyl Stair Treads
-----------------------------------	---

Site Requirements	Before beginning the maintenance procedures, be sure to take proper safety precautions and have appropriate wet floor signage. Ensure that all adhesive curing times have been met prior to conducting initial maintenance, as cleaning products may disrupt the adhesive bond. Refer to specific care & maintenance guides for the flooring product for recommendations for cleaning.
--------------------------	--

Mixing / Dilution Ratios	Choose the proper dilution ratio for the situation according to the care & maintenance information. Areas with a high number of finish layers require more chemistry per gallon of water. Areas with 1-5 coats of finish use 32 oz. per gallon of clean potable water.
---------------------------------	---



FR-920 Finish Remover

MAINTENANCE PRODUCTS TECHNICAL DATA

Areas with more than 5 known layers of finish may require more FR-920 per gallon of water. Do not use more than 64 oz. per gallon of clean potable water.

Rinsing with clean water is required to ensure no chemistry is left behind.

Disposal

Disposal in accordance with local, state and federal regulations.

Do not allow product to get into drains, watercourses, or landfills.

Hardened product residues are considered construction waste.

Empty packaging is recyclable.

California Prop 65 Labeling

To the best of our knowledge, this product does not contain any of the listed chemicals, which the state of California has found to cause cancer, birth defects or other reproductive harm

Product Warranty

1 Year Manufacturers Warranty

Technical Support

solutions@rhctechnical.com

Product Support

solutions@rhctechnical.com

Technical Documentation

www.excelsiorproducts.net