



MF-940 Matte Floor Finish

MAINTENANCE PRODUCTS TECHNICAL DATA

Excelsior MF-940 Matte Acrylic Floor Finish is a durable scuff resistance non-reflective matte acrylic floor finish developed for resilient flooring products

Product Type	Matte Finish Acrylic Floor Finish
Characteristics	White, Opaque Liquid
Packaging	1 Gallon Unit
ASTM D7149 - Freeze Thaw Stability	Do Not Allow to Freeze
SCAQMD Rule 1113	≤ 0.1 grams/liter VOC Content
ASTM D2047 - Static Coefficient of Friction	≥ 0.5
<i>ADA Standards for Accessible Design states the floor surface shall be stable, firm and slip resistant. Our test results utilize the James Machine as described in D2047 and as described in UL410 for floor covering materials (FCM) utilizing a neolite foot under dry conditions. Maintenance processes and commonly utilized site applied finishes, polishes and other sealers to maintain resilient flooring products will change the walking surface and ultimately the Static Coefficient of Friction.</i>	
pH	8.5
Dilution Ratio	Ready to Use
Coverage Range	2500 - 3000 sq. ft. per Gallon
<i>Coverages will vary depending upon dilution rate, flooring surface and applicator. Initial coats will utilize more materials than subsequent coats</i>	
Application Method	Micro-Fiber Flat Mop / String Finish Mop
Dry Time	≤ 45 Minutes
<i>Dry time will vary with conditions; higher temps with higher humidity will be longer than lower temps with lower humidity</i>	
Access Times After Application	Light Foot Traffic ≥ 1 Hour Heavy Foot Traffic ≥ 12 Hours
<i>Access time will vary with conditions; higher temps with higher humidity will be longer than lower temps with lower humidity</i>	
Shelf Life	18 Months from Manufacturing Date

Reading the Date Code 12321

The first 3 numbers indicate the Julian date of production (123), the last 2 numbers indicate the year (21)

On the carton it is printed on the upper right corner on a side panel

On the bottle it is printed above the label

Service & Storage Temperature	60° - 85° F
--	-------------

Shelf Life depends on proper storage within service & storage temperatures in unopened container

The following information is provided as general guidance, always refer to the current care & maintenance information on the product website for the resilient flooring being maintained for complete and detailed information

Approved Flooring Products	Rubber Tiles & Sheet LVT/LVP Solid Vinyl Tiles
-----------------------------------	--

Site Requirements	Before beginning the maintenance procedures, be sure to take proper safety precautions and have appropriate wet floor signage. Ensure that all adhesive curing times have been met prior to conducting initial maintenance, as cleaning products may disrupt the adhesive bond.
--------------------------	--



MF-940 Matte Floor Finish

MAINTENANCE PRODUCTS TECHNICAL DATA

Refer to specific care & maintenance guides for the flooring product for recommendations for cleaning.

Application

Apply in thin, even coats using a micro-fiber flat mop or string finish mop.

Check the care & maintenance guidelines for the flooring regarding the number of coats to apply.

Ensure that each coat it completely dry prior to applying the subsequent coats.

Disposal

Disposal in accordance with local, state and federal regulations.

Do not allow product to get into drains, watercourses, or landfills.

Hardened product residues are considered construction waste.

Empty packaging is recyclable.

California Prop 65 Labeling

To the best of our knowledge, this product does not contain any of the listed chemicals, which the state of California has found to cause cancer, birth defects or other reproductive harm

Product Warranty

1 Year Manufacturers Warranty

Technical Support

solutions@rhctechnical.com

Product Support

solutions@rhctechnical.com

Technical Documentation

www.excelsiorproducts.net