



NC-900 Neutral Cleaner

MAINTENANCE PRODUCTS TECHNICAL DATA

Excelsior NC-900 Neutral Cleaner is a pH neutral cleaner for the initial and daily cleaning of Resilient flooring products

| | |
|---|---|
| Product Type | Neutral Floor Cleaner for Resilient Floor Coverings |
| Characteristics | Clear, Colorless Liquid |
| Packaging | 1 Gallon Unit |
| ASTM D7149 - Freeze Thaw Stability | Up to 5 Cycles, Down to 0° F |
| SCAQMD Rule 1113 | ≤ 0.1 grams/liter VOC Content |
| pH | 7, When Properly Diluted |
| Dilution Ratio | 2 - 4 oz. per Gallon |
| Coverage Range | 250 - 350 sq. ft. per Diluted Gallon |
| <i>Coverages will vary depending upon dilution rate, flooring surface and applicator.</i> | |
| Application Method | Pump-Up Sprayer, String Mop, or Auto Scrubber |
| Dwell Time | 5 - 10 Minutes |
| Shelf Life | 18 Months from Manufacturing Date |

Reading the Date Code 12321

The first 3 numbers indicate the Julian date of production (123), the last 2 numbers indicate the year (21)

On the carton it is printed on the upper right corner on a side panel

On the bottle it is printed above the label

| | |
|--|-------------|
| Service & Storage Temperature | 60° - 85° F |
|--|-------------|

Shelf Life depends on proper storage within service & storage temperatures in unopened container

The following information is provided as general guidance, always refer to the current care & maintenance information on the product website for the resilient flooring being maintained for complete and detailed information

| | |
|-----------------------------------|---|
| Approved Flooring Products | Rubber Tiles & Sheet LVT/LVP Solid Vinyl Tiles Quartz Flooring Resilient Stair Treads Multipurpose Athletic Flooring Bonded Rubber Crumb Flooring |
|-----------------------------------|---|

| | |
|--------------------------|--|
| Site Requirements | Before beginning the maintenance procedures, be sure to take proper safety precautions and have appropriate wet floor signage. Ensure that all adhesive curing times have been met prior to conducting initial maintenance, as cleaning products may disrupt the adhesive bond. Refer to specific care & maintenance guides for the flooring product for recommendations for cleaning. |
|--------------------------|--|



NC-900 Neutral Cleaner

MAINTENANCE PRODUCTS TECHNICAL DATA

| | |
|------------------------------------|--|
| Mixing / Dilution Ratios | <p>Choose the proper dilution ratio for the situation according to the care & maintenance information.</p> <p>Higher soil levels require more chemistry per gallon of clean water. Be advised that using too much chemistry can result in tackiness of the flooring surface without proper and adequate rinsing.</p> <p>If performing Initial Maintenance, it is recommended to start at 2 oz. per gallon of clean potable water.</p> <p>If performing Daily, Routine or Periodic Maintenance, it is recommended to start at 2 oz. per gallon of clean potable water.</p> <p>Increased soil levels may require up to 4 oz. per gallon of clean potable water.</p> <p>Heavy soil levels may require more than one attempt to clean.</p> <p>Rinsing with clean water is required to ensure no chemistry is left behind.</p> |
| Disposal | <p>Disposal in accordance with local, state and federal regulations.</p> <p>Do not allow product to get into drains, watercourses, or landfills.</p> <p>Hardened product residues are considered construction waste.</p> <p>Empty packaging is recyclable.</p> |
| California Prop 65 Labeling | <p>To the best of our knowledge, this product does not contain any of the listed chemicals, which the state of California has found to cause cancer, birth defects or other reproductive harm</p> |
| Product Warranty | <p>1 Year Manufacturers Warranty</p> |
| Technical Support | <p>solutions@rhctechnical.com</p> |
| Product Support | <p>solutions@rhctechnical.com</p> |
| Technical Documentation | <p>www.excelsiorproducts.net</p> |
