



# PR-930 Performance Remover

MAINTENANCE PRODUCTS TECHNICAL DATA

**Excelsior PR-930 Performance Remover** is a finish remover specifically designed to remove topically applied flooring finishes from resilient flooring products that are sensitive to alkalinity, such as rubber flooring and crumb/recycled rubber flooring products

<b>Product Type</b>	Finish Remover for Rubber Floor Coverings
<b>Characteristics</b>	Clear, Colorless Liquid
<b>Packaging</b>	1 Gallon Unit
<b>ASTM D7149 - Freeze Thaw Stability</b>	Up to 5 Cycles, Down to 0° F
<b>SCAQMD Rule 1113</b>	≤ 0.1 grams/liter VOC Content
<b>pH</b>	10.5, When Properly Diluted
<b>Dilution Ratio</b>	32 - 64 oz. per Gallon
<b>Coverage Range</b>	100 - 150 sq. ft. per Diluted Gallon
<i>Coverages will vary depending upon dilution rate, flooring surface and applicator.</i>	
<b>Application Method</b>	Pump-Up Sprayer, String Mop
<b>Dwell Time</b>	5 - 10 Minutes
<i>Dwell time will vary with conditions; additional layers of finish will require additional time to break down the finish for removal.</i>	
<b>Shelf Life</b>	18 Months from Manufacturing Date

### Reading the Date Code 12321

The first 3 numbers indicate the Julian date of production (123), the last 2 numbers indicate the year (21)

On the carton it is printed on the upper right corner on a side panel

On the bottle it is printed above the label

<b>Service &amp; Storage Temperature</b>	60° - 85° F
--	-------------

*Shelf Life depends on proper storage within service & storage temperatures in unopened container*

*The following information is provided as general guidance, always refer to the current care & maintenance information on the product website for the resilient flooring being maintained for complete and detailed information*

<b>Approved Flooring Products</b>	Rubber Tiles & Sheet Resilient Stair Treads Multipurpose Athletic Flooring Bonded Rubber Crumb Flooring
-----------------------------------	--

<b>Site Requirements</b>	Before beginning the maintenance procedures, be sure to take proper safety precautions and have appropriate wet floor signage. Ensure that all adhesive curing times have been met prior to conducting initial maintenance, as cleaning products may disrupt the adhesive bond. Refer to specific care & maintenance guides for the flooring product for recommendations for cleaning.
--------------------------	--



# PR-930 Performance Remover

## MAINTENANCE PRODUCTS TECHNICAL DATA

---

### Mixing / Dilution Ratios

Choose the proper dilution ratio for the situation according to the care & maintenance information.

Areas with a high number of finish layers require more chemistry per gallon of water. Areas with 1-5 coats of finish use 32 oz. per gallon of clean potable water.

Areas with more than 5 known layers of finish may require more PR-930 per gallon of water. Do not use more than 64 oz. per gallon of clean potable water.

**Rinsing with clean water is required to ensure no chemistry is left behind.**

---

### Disposal

Disposal in accordance with local, state and federal regulations.

Do not allow product to get into drains, watercourses, or landfills.

Hardened product residues are considered construction waste.

Empty packaging is recyclable.

---

### California Prop 65 Labeling

To the best of our knowledge, this product does not contain any of the listed chemicals, which the state of California has found to cause cancer, birth defects or other reproductive harm

---

### Product Warranty

1 Year Manufacturers Warranty

---

### Technical Support

[solutions@rhctechnical.com](mailto:solutions@rhctechnical.com)

---

### Product Support

[solutions@rhctechnical.com](mailto:solutions@rhctechnical.com)

---

### Technical Documentation

[www.excelsiorproducts.net](http://www.excelsiorproducts.net)