



# ASD-800 ESD Adhesive

TECHNICAL DATA

**Excelsior ASD-800 ESD Adhesive** is an acrylic wet-set conductive adhesive specifically designed for the permanent installation of ESD rubber and vinyl flooring products over porous substrates in indoor applications; it is a low odor, non-flammable, solvent-free product and ready to use product

<b>Product Type</b>	Wet-Set Conductive Acrylic ESD Adhesive for porous (absorptive) surfaces
<b>Characteristics</b>	Grey Paste
<b>Packaging</b>	1 Gallon Unit 2 Gallon Unit
<b>Sustainability Information</b>	Made in the U.S.A. Meets Buy America Act (49 CFR Part 661) Meets Buy American Act (41 USC §§ 8301-8303) Contributes to LEED v4/4.1 ≤1 grams/liter VOC Content (SCAQMD RULE 1168) Meets SCAQMD Rule 1168 Requirements FloorScore Certified Meets CA 01350 Requirements HPD Available Red List Chemical Free Contains No Recycled Content Manufacturers Product certified Cradle to Cradle Gold
<b>Moisture Control Properties</b>	Not a moisture inhibitor or mitigation product
<b>ASTM F2170 - RH Limit</b>	90%, <i>in situ</i>
<b>ASTM F1869 - MVER Limit</b>	6 lbs. / 1000 sq. ft. / 24 hours
<b>ASTM F710 - pH Limit</b>	≥ 7 - ≤ 10
<b>ASTM D7149 - Freeze Thaw Stability</b>	Up to 5 Cycles, Down to 0° F
<b>ASTM D1337 - Shelf Life</b>	2 Years from Manufacturing Date
<b>Reading the Date Code</b>	B210201515293 Ignore the B, focus on the 210201 which is Year (21) Month (02) and Day (01), ignore the balance as it is for batching information for manufacturer Located on the lower left corner of the label under the UPC code
<i>Shelf Life depends on proper storage within service &amp; storage temperatures in unopened container</i>	
<b>Conductivity/Surface Resistance</b>	Ultimate - ≤ 100 k-ohms @ 36" Electrode Distance
<b>ASTM D6004 - Adhesive Sheer Resistance</b>	Excellent
<b>ASTM D6862 - 90° Peel Resistance</b>	Excellent



# ASD-800 ESD Adhesive

TECHNICAL DATA

<b>ASTM D7888 - Plasticizer Resistance</b>	Excellent
<b>California Prop 65</b>	To the best of our knowledge, this product does not contain any of the listed chemicals, which the state of California has found to cause cancer, birth defects or other reproductive harm
<b>Application Method</b>	Trowel Applied
<b>Trowel Size &amp; Coverages</b>	
<b>(Absorptive) Porous Substrates</b>	1/16" x 1/16" x 1/16" V Notch, 160 sq. ft. per Gallon
<b>Flash Time</b>	
<b>(Absorptive) Porous Substrates</b>	5 - 10 Minutes
<b>Working Time</b>	
<b>(Absorptive) Porous Substrates</b>	50 - 60 Minutes
<i>Trowel notch dimensions are Width x Depth x Separation</i>	
<i>Coverage rates are approximate and subject to level of porosity as well as ambient conditions as well as angle of the trowel, actual values may vary from stated amounts</i>	
<i>Flash time and working time will vary with conditions; higher temps with higher humidity will be shorter than lower temps with lower humidity</i>	
<b>Access Times During &amp; After Installation</b>	
<b>Heat Welding</b>	24 Hours
<b>Light Foot Traffic</b>	24 Hours
<b>Heavy Foot Traffic</b>	48 Hours
<b>Rolling Loads</b>	72 Hours
<b>Maintenance</b>	72 Hours
<b>Service &amp; Storage Temperature</b>	65° - 85° F
<b><i>The following information is provided as general guidance, always refer to the current installation information on the product website for the resilient flooring being installed for complete information</i></b>	
<b>Approved Flooring Products</b>	ESD Rubber Tiles ESD Vinyl Tiles
<b>Approved Substrates &amp; Surfaces</b>	Concrete above, on, or below grade; properly prepared for moisture sensitive resilient flooring in place a minimum of 45 days APA rated plywood underlayment Properly prepared Portland cement based patches & underlayments Radiant heated sub-floors
<b>Site Requirements</b>	During acclimation, the site must be fully enclosed, weather tight, and material must be in the installation area with the HVAC system functional and operating at desired service temperatures for a period of 48 hours prior to installation, during the installation and for the service life of the installation afterwards.

<b>Site Requirements...</b>	It is recommended to maintain an ambient relative humidity between 40% and 60% for a period of 48 hours prior to installation, during the installation and for the service life of the installation afterwards.
<b>Substrate Requirements</b>	<p>All substrates must be prepared according to the following information or ASTM F710 or ASTM F1482 at a minimum, as well as applicable ACI and RFCI guidelines.</p> <p>Concrete substrates, whether on-grade and/or below grade must have an intact and effective moisture vapor barrier which meets the current requirements of ASTM E1745</p> <p>Substrates must be clean, smooth, permanently dry, flat, and structurally sound.</p> <p>Substrates must be free of visible water or moisture, dust, sealers, paint, sweeping compounds, curing compounds, residual adhesives and adhesive removers, concrete hardeners or densifiers, solvents, wax, oil, grease, asphalt, visible alkaline salts or excessive efflorescence, mold, mildew and any other extraneous coating, film, material or foreign matter.</p>
<b>Adhesive Clean-Up</b>	<p>Uncured Adhesive can be removed with solution of 70% isopropyl alcohol and a clean cloth</p> <p>Cured adhesive will be difficult to remove from wall and flooring surfaces, ensure removal prior to curing</p>
<b>Product &amp; Substrate Restrictions</b>	<p>Not designed for use with products manufactured with polyolefin, polyethylene, or polypropylene</p> <p>Not designed for use on substrates that have been exposed to adhesive removers, solvents, or chemical cleaners</p>
<b>Disposal</b>	<p>Dispose in accordance with local, state and federal regulations.</p> <p>Do not allow product to get into drains, watercourses or landfill.</p> <p>Hardened product residues are considered construction waste.</p> <p>Empty packaging is recyclable.</p>
<b>Warranty</b>	<p>1 Year Manufacturer's Warranty</p> <p>Bond Warranty determined by Warranty of product being installed, see warranty document for details</p>
<b>Technical Support</b>	<a href="mailto:solutions@rhctechnical.com">solutions@rhctechnical.com</a>
<b>Product Support</b>	<a href="mailto:solutions@rhctechnical.com">solutions@rhctechnical.com</a>
<b>Technical Documentation</b>	<a href="http://www.excelsiorproducts.net">www.excelsiorproducts.net</a>